



Double link wheel with brake, plate, wheel diameter 200 mm, building height 250 mm, hub in aluminum with soft track in PUR in orange. 1400 kg load capacity, double ball bearings

Artikelnr P2001781

Material Länkhjul

Tekniska egenskaper

Wheel

| Egenskap | Värde | Enhet | Provningsstandard |
|---------------------|-----------------|-------|-------------------|
| Link wheel diameter | 200 | mm | |
| Wheel Storage | Dubbla kullager | | |
| Track width | 50 | mm | |

Load-bearing capacity

| Egenskap | Värde | Enhet | Provningsstandard |
|--------------------------|-------|-------|-------------------|
| Link wheel load capacity | 1400 | kg | |

Type of mounting

| Egenskap | Värde | Enhet | Provningsstandard |
|-----------------|-----------|-------|-------------------|
| Hinge type | Broms | | |
| Mounting Method | Topplatta | | |

Track

| Egenskap | Värde | Enhet | Provningsstandard |
|----------------------------|-------------|-------|-------------------|
| Chain Wheel Material Track | PUR | | |
| Banana Hardness | 93° Shore A | | |
| Banana color | Orange | | |

Bracket

| Egenskap | Värde | Enhet | Provningsstandard |
|-----------------|---------|-------|-------------------|
| Building height | 250 | mm | |
| Plate size | 150x110 | | |
| Drill pattern | 105x80 | | |
| Hole Diameter | 12 | mm | |

Hub

| Egenskap | Värde | Enhet | Provningsstandard |
|--------------|-----------|-------|-------------------|
| Material Hub | Aluminium | | |

Hinge Material

| Egenskap | Värde | Enhet | Provningsstandard |
|------------------|-------|-------|-------------------|
| Material Bracket | Stål | | |