



Electrically conductive fixed bracket, flat, wheel diameter 160 mm, construction height 195 mm, hub in aluminum with soft running surface in PUR in grå. 350 kg load capacity, double ball bearings

Artikelnr P2000556

Material Fast bygel

Tekniska egenskaper

Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	160	mm	
Wheel Storage	Dubbla kullager		
Track width	50	mm	

Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	350	kg	

Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	PUR		
Banana Hardness	80° Shore A		
Banana color	Grå		

Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	195	mm	
Plate size	140x110		
Drill pattern	105x80		
Hole Diameter	11x14	mm	

Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	Aluminium		

Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	Plåt		