



Electrically conductive fixed bracket, flat, wheel diameter 50 mm, construction height 66 mm, hub in PP with soft running surface in TPE in grå. 40 kg load capacity, slide bearings

Artikelnr P2000231

Material Fast bygel

Tekniska egenskaper

Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	50	mm	
Wheel Storage	Glidlager		
Track width	20	mm	

Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	40	kg	

Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	TPE		
Banana Hardness	85° Shore A		
Banana color	Grå		

Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	66	mm	
Plate size	51x42		
Drill pattern	38x27		
Hole Diameter	6.1	mm	

Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	PP		

Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	Plåt		