



Fixed bracket, flat, wheel diameter 100 mm, construction height 132 mm, hub in PA6 with soft running surface in ElastoGum in grå. 225 kg load capacity, ball bearing

Artikelnr P2000520
Material Fast bygel

Tekniska egenskaper

Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	100	mm	
Wheel Storage	Kullager		
Track width	36	mm	

Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	225	kg	

Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	ElastoGum		
Banana Hardness	75° Shore A		
Banana color	Grå		

Temperature Range

Egenskap	Värde	Enhet	Provningsstandard
Lowest temperature	-20	°C	
Maximum Short-term Temperature	60	°C	

Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	132	mm	
Plate size	105x85		
Drill pattern	80x60		
Hole Diameter	12.5x9	mm	

Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	PA6		

Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	Plåt		