



Fixed bracket, flat, wheel diameter 100 mm, construction height 145 mm, hub in aluminium with soft running surface in PUR in orange. 400 kg load capacity, double ball bearing

Artikelnr P2001649
Material Fast bygel

Tekniska egenskaper

Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	100	mm	
Wheel Storage	Dubbla kullager		
Track width	50	mm	

Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	400	kg	

Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	PUR		
Banana Hardness	93° Shore A		
Banana color	Orange		

Temperature Range

Egenskap	Värde	Enhet	Provningsstandard
Lowest temperature	-20	°C	
Maximum Short-term Temperature	70	°C	

Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	145	mm	
Plate size	140x110		
Drill pattern	105x80		
Hole Diameter	11	mm	

Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	Aluminium		

Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	Stål		