



Fixed bracket, flat, wheel diameter 125 mm, construction height 157 mm, hub in PA6 with soft running surface in PUR in blå. 160 kg load capacity, ball bearing

Artikelnr P2000498

Material Fast bygel

Tekniska egenskaper

Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	125	mm	
Wheel Storage	Kullager		
Track width	36	mm	

Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	160	kg	

Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	PUR		
Banana Hardness	98° Shore A		
Banana color	Blå		

Temperature Range

Egenskap	Värde	Enhet	Provningsstandard
Lowest temperature	-30	°C	
Maximum Short-term Temperature	70	°C	

Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	157	mm	
Plate size	105x85		
Drill pattern	80x60		
Hole Diameter	12x9	mm	

Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	PA6		

Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	Plåt		