



## Fixed bracket, flat, wheel diameter 125 mm, construction height 163 mm, hub in PA6 with soft running surface in PUR in röd. 300 kg load capacity, double ball bearing

Artikelnr P2001149

Material Fast bygel

### Tekniska egenskaper

#### Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	125	mm	
Wheel Storage	Dubbla kullager		
Track width	45	mm	

#### Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	300	kg	

#### Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

#### Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	PUR		
Banana Hardness	98° Shore A		
Banana color	Röd		

### Temperature Range

Egenskap	Värde	Enhet	Provningsstandard
Lowest temperature	<b>-20</b>	°C	
Maximum Short-term Temperature	<b>70</b>	°C	

### Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	<b>163</b>	mm	
Plate size	<b>140x110</b>		
Drill pattern	<b>105x80</b>		
Hole Diameter	<b>11</b>	mm	

### Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	<b>PA6</b>		

### Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	<b>Plåt</b>		