



Fixed bracket, flat, wheel diameter 125 mm, construction height 165,5 mm, hard wheel in solid PA6, 400 kg load capacity, double ball bearing

Artikelnr P2001304

Material Fast bygel

Tekniska egenskaper

Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	125	mm	
Wheel Storage	Dubbla kullager		
Track width	45	mm	

Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	400	kg	

Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	PA6		
Banana Hardness	83° Shore D		
Banana color	Natur		

Temperature Range

Egenskap	Värde	Enhet	Provningsstandard
Lowest temperature	-20	°C	
Maximum Short-term Temperature	70	°C	

Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	165.5	mm	
Plate size	140x110		
Drill pattern	105x80		
Hole Diameter	11	mm	

Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	PA6		

Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	Plåt		