



## Fixed bracket, flat, wheel diameter 150 mm, construction height 200 mm, hard wheel in solid PA6, 1500 kg load capacity, double ball bearing

Artikelnr P2001658

Material Fast bygel

### Tekniska egenskaper

#### Wheel

Egenskap	Värde	Enhet	Provningsstandard
Link wheel diameter	150	mm	
Wheel Storage	Dubbla kullager		
Track width	55	mm	

#### Load-bearing capacity

Egenskap	Värde	Enhet	Provningsstandard
Link wheel load capacity	1500	kg	

#### Type of mounting

Egenskap	Värde	Enhet	Provningsstandard
Hinge type	Fast		
Mounting Method	Topplatta		

#### Track

Egenskap	Värde	Enhet	Provningsstandard
Chain Wheel Material Track	PA6 C		
Banana Hardness	85° Shore D		
Banana color	Natur		

#### Temperature Range

Egenskap	Värde	Enhet	Provningsstandard
Lowest temperature	<b>-20</b>	°C	
Maximum Short-term Temperature	<b>70</b>	°C	

### Bracket

Egenskap	Värde	Enhet	Provningsstandard
Building height	<b>200</b>	mm	
Plate size	<b>140x110</b>		
Drill pattern	<b>105x80</b>		
Hole Diameter	<b>11</b>	mm	

### Hub

Egenskap	Värde	Enhet	Provningsstandard
Material Hub	<b>PA6 C</b>		

### Hinge Material

Egenskap	Värde	Enhet	Provningsstandard
Material Bracket	<b>Stål</b>		