



# PA6 GL 2000x1000x15 mm gr  n

Artikelnr P1600231

## 1. Tekniskt datablad

| Egenskap                                   | V  rde   | Enhet       | Standard          |
|--------------------------------------------|----------|-------------|-------------------|
| Density                                    | 1.1      | g/cm        | DIN EN ISO 1183-1 |
| Tensile Strength                           | 67.5     | MPa         | DIN EN ISO 527    |
| Modulus of elasticity (tensile)            | 3000     | MPa         | DIN EN ISO 527    |
| Break Elongation                           | 198.5    | %           | DIN EN ISO 527    |
| Melting point                              | 218      |   C         | ISO 11357-3       |
| Maximal operating temperature (short-term) | 162.5    |   C         |                   |
| Maximum Operating Temperature              | 109      |   C         |                   |
| Minimum temperature                        | -40      |   C         |                   |
| Heat deflection temperature (HDT/A)        | 90       |   C         | ISO 75            |
| Dielectric Strength                        | 20       | kV/mm       | IEC 60243         |
| Volume Resistivity                         | 10       |             | DIN EN 62631-3-1  |
| Dielectric Constant (1 MHz)                | 3.7      | -           | IEC 60250         |
| Dielectric loss factor (100 Hz)            | 0.02     | -           | IEC 60250         |
| Thermal Conductivity                       | 0.3      | W/(m   K)   | DIN 52612-1       |
| Surface Resistivity                        | 10       |             | DIN EN 62631-3-2  |
| Comparative Tracking Index (CTI)           | 600      | V           | IEC 60112         |
| Water absorption to saturation             | 5.65     | %           | DIN EN ISO 62     |
| Water Absorption to Saturation             | 5.65     | %           | DIN EN ISO 62     |
| Notched impact strength (Charpy)           | 13       | kJ/m        | DIN EN ISO 179    |
| Thermal Expansion Coefficient              | 0.7      | 10      /K  | DIN 53752         |
| Hardness Shore D                           | 81       |     Shore D | ISO 868           |

## 2. Kemisk best  ndighet

   Best  ndig    Delvis best  ndig    Ej best  ndig

| Kemikalie   | Konc. | Resultat |
|-------------|-------|----------|
| 1,4-Dioxane | 100   |          |

| Kemikalie               | Konc.   | Resultat    |
|-------------------------|---------|-------------|
| 2-Hydroxypropionic Acid | 90      | <div></div> |
| Acetic Acid             | 100     | <div></div> |
| Acetone                 | 100     | <div></div> |
| Ammonia                 | conc.   | <div></div> |
| Ammonium Chloride       | â€”     | <div></div> |
| Amyl Alcohol            | â€”     | <div></div> |
| Apple Juice             | â€”     | <div></div> |
| Benzene                 | â€”     | <div></div> |
| Bleaching Solution      | 12.5 cl | <div></div> |
| Boric Acid              | 100     | <div></div> |
| Brake Fluid             | â€”     | <div></div> |
| Butyl Acetate           | â€”     | <div></div> |
| Calcium Chloride        | â€”     | <div></div> |
| Carbon Disulfide        | 100     | <div></div> |
| Carbon Tetrachloride    | â€”     | <div></div> |
| Chlorine (gas)          | 100     | <div></div> |
| Chlorobenzene           | 100     | <div></div> |
| Chloroform              | â€”     | <div></div> |
| Citric Acid             | 10      | <div></div> |
| Cresol                  | â€”     | <div></div> |
| Cyclohexanone           | 100     | <div></div> |
| Cyclohexene             | 100     | <div></div> |
| Diesel Fuel             | â€”     | <div></div> |
| Diethylene Oxide        | â€”     | <div></div> |
| Ethyl Acetate           | 100     | <div></div> |
| Ethyl Alcohol           | 96      | <div></div> |
| Ethylene Chloride       | 100     | <div></div> |
| Food Oil                | â€”     | <div></div> |
| Formaldehyde (aqueous)  | 40      | <div></div> |
| Formic Acid             | 10      | <div></div> |
| Frost Protection Agent  | â€”     | <div></div> |
| Fuel (aromatic free)    | â€”     | <div></div> |
| Glycerine               | 100     | <div></div> |
| Glycol                  | 100     | <div></div> |

| Kemikalie                        | Konc.       | Resultat |
|----------------------------------|-------------|----------|
| Heating Oil                      | â€”         | ●        |
| Heptane                          | 100         | ●        |
| Hydrochloric Acid                | 10          | ●        |
| Hydrochloric Acid (concentrated) | conc.       | ●        |
| Hydrofluoric Acid                | 40          | ●        |
| Hydrogen Peroxide                | 10          | ●        |
| Hydrogen Sulfide (aqueous)       | â€”         | ●        |
| Isopropyl Alcohol                | 100         | ●        |
| Linseed Oil                      | â€”         | ●        |
| Mercurochrome                    | â€”         | ●        |
| Methyl Alcohol                   | 100         | ●        |
| Methyl Ethyl Ketone (MEK)        | 100         | ●        |
| Methylene Chloride               | 100         | ●        |
| Milk                             | â€”         | ●        |
| Mineral Oils (aromatic free)     | â€”         | ●        |
| Nitric Acid                      | 10          | ●        |
| Nitric Acid                      | 50          | ●        |
| Nitrobenzene                     | â€”         | ●        |
| Oxalic Acid                      | â€”         | ●        |
| Ozone Gas                        | â‰‰ 0.5 ppm | ●        |
| Paraffine Oil                    | 100         | ●        |
| Perchloroethylene                | â€”         | ●        |
| Petroleum                        | 100         | ●        |
| Petroleum Ether                  | 100         | ●        |
| Phenol (aqueous)                 | ca. 9       | ●        |
| Phosphoric Acid                  | 50          | ●        |
| Potassium Hydroxide liquor       | 50          | ●        |
| Premium Fuel                     | â€”         | ●        |
| Propyl Alcohol                   | â€”         | ●        |
| Pyridine                         | â€”         | ●        |
| Silicone Oil                     | â€”         | ●        |
| Sodium Carbonate (aqueous)       | â€”         | ●        |
| Sodium Chloride (aqueous)        | â€”         | ●        |
| Sodium Hydrogen Sulfite          | â€”         | ●        |
| Sodium Hydroxide liquor          | 60          | ●        |

| Kemikalie                | Konc.  | Resultat    |
|--------------------------|--------|-------------|
| Sodium Hydroxide liquor  | 15     | <div></div> |
| Sodium Nitrate (aqueous) | â€”    | <div></div> |
| Sodium Thiosulfate       | â€”    | <div></div> |
| Sulfuric Acid            | 96     | <div></div> |
| Tetrahydrofuran (THF)    | 100    | <div></div> |
| Toluene                  | 100    | <div></div> |
| Transformer Oil          | â€”    | <div></div> |
| Trichloroethylene        | 100    | <div></div> |
| Vinegar (standard)       | 5 - 10 | <div></div> |
| Water                    | â€”    | <div></div> |
| Xylene                   | â€”    | <div></div> |