



PPS 3000x610x40 mm svart

Artikelnr P1010421

Beständig

Delvis beständig

Ej beständig

Kemikalie	Koncentration	Temp.	Beständighet
1,4-Dioxane	100	20 Å°C	
Acetone	100	20 Å°C	
Ammonia	â€”	20 Å°C	
Ammonium chloride	â€”	20 Å°C	
Benzene	â€”	20 Å°C	
Brake fluid	â€”	20 Å°C	
Butyl acetate	â€”	20 Å°C	
Calcium chloride	â€”	20 Å°C	
Carbon tetrachloride	â€”	20 Å°C	
Chlorobenzene	100	20 Å°C	
Chloroform	â€”	20 Å°C	
Diesel	â€”	20 Å°C	
Diethylene oxide	â€”	20 Å°C	
Ethyl acetate	100	20 Å°C	
Ethyl alcohol (ethanol)	96	20 Å°C	
Frost protection agent	â€”	20 Å°C	
Fuel, aromatic free	â€”	20 Å°C	
Glycerine	100	20 Å°C	
Hydrochloric acid (10%)	10	20 Å°C	
Hydrochloric acid (concentrated)	â€”	20 Å°C	
Isopropyl alcohol	100	20 Å°C	
Methyl alcohol (methanol)	100	20 Å°C	
Methyl ethyl ketone (MEK)	100	20 Å°C	
Methylene chloride	100	20 Å°C	
Mineral oils (aromatic free)	â€”	20 Å°C	
Nitric acid (10%)	10	20 Å°C	
Nitric acid (50%)	50	20 Å°C	

Kemikalie	Koncentration	Temp.	Best�ndighet
Perchloroethylene	��	20 ��C	�
Phenol, aqueous	9	20 ��C	�
Phosphoric acid	50	20 ��C	�
Premium fuel	��	20 ��C	�
Sodium chloride, aqueous	��	20 ��C	�
Sodium hydroxide solution (15%)	15	20 ��C	�
Sodium hydroxide solution (60%)	60	20 ��C	�
Sulphuric acid	96	20 ��C	�
Tetrahydrofuran (THF)	100	20 ��C	�
Toluene	100	20 ��C	�
Transformer oil	��	20 ��C	�
Trichloroethylene	100	20 ��C	�
Water	��	20 ��C	�
Xylene	��	20 ��C	�