



PSU 20x3000 mm gul

Artikelnr P1010447

Beständig Delvis beständig Ej beständig

Kemikalie	Koncentration	Temp.	Beständighet
Acetic acid	100	20 Å°C	
Acetone	100	20 Å°C	
Ammonia	â€	20 Å°C	
Benzene	â€	20 Å°C	
Butyl acetate	â€	20 Å°C	
Calcium chloride	â€	20 Å°C	
Carbon tetrachloride	â€	20 Å°C	
Chlorobenzene	100	20 Å°C	
Chloroform	â€	20 Å°C	
Citric acid	10	20 Å°C	
Cyclohexene	100	20 Å°C	
Diesel	â€	20 Å°C	
Diethylene oxide	â€	20 Å°C	
Ethyl acetate	100	20 Å°C	
Ethyl alcohol (ethanol)	96	20 Å°C	
Food oil	â€	20 Å°C	
Frost protection agent	â€	20 Å°C	
Fuel (aromatic free)	â€	20 Å°C	
Fuel oil	â€	20 Å°C	
Glycerine	100	20 Å°C	
Glycol	100	20 Å°C	
Heptane	100	20 Å°C	
Hydrochloric acid	10	20 Å°C	
Hydrochloric acid (concentrated)	â€	20 Å°C	
Hydrofluoric acid	40	20 Å°C	
Hydrogen peroxide	10	20 Å°C	
Isopropyl alcohol	100	20 Å°C	

Kemikalie	Koncentration	Temp.	Best�ndighet
Methyl alcohol (methanol)	100	20 �C	�
Methyl ethyl ketone (MEK)	100	20 �C	�
Methylene chloride	100	20 �C	�
Milk	��	20 �C	�
Mineral oils (aromatic free)	��	20 �C	�
Nitric acid	10	20 �C	�
Oxalic acid	��	20 �C	�
Perchloroethylene	��	20 �C	�
Phosphoric acid	50	20 �C	�
Silicone oil	��	20 �C	�
Sodium carbonate (aqueous)	��	20 �C	�
Sodium chloride (aqueous)	��	20 �C	�
Sodium hydroxide solution (60%)	60	20 �C	�
Sodium hydroxide solution (caustic soda)	15	20 �C	�
Sulphuric acid	96	20 �C	�
Toluene	100	20 �C	�
Transformer oil	��	20 �C	�
Trichloroethylene	100	20 �C	�
Vinegar (standard)	5-10	20 �C	�
Water	��	20 �C	�
Xylene	��	20 �C	�