

# PMMA E 3050x2050x6 mm transparente 92%

Artikelnr P1200673

Beständig Delvis beständig Ej beständig

| Kemikalie               | Concentration | Temp.  | Beständighet |
|-------------------------|---------------|--------|--------------|
| Acetic acid             | 100%          | 20 Å°C |              |
| Acetone                 | 100%          | 20 Å°C |              |
| Ammonia                 | conc.         | 20 Å°C |              |
| Amyl alcohol            | â€”           | 20 Å°C |              |
| Apple juice             | â€”           | 20 Å°C |              |
| Benzene                 | â€”           | 20 Å°C |              |
| Butyl acetate           | â€”           | 20 Å°C |              |
| Calcium chloride        | â€”           | 20 Å°C |              |
| Carbon disulphide       | 100%          | 20 Å°C |              |
| Carbon tetrachloride    | â€”           | 20 Å°C |              |
| Chlorine gas            | 100%          | 20 Å°C |              |
| Chloroform              | â€”           | 20 Å°C |              |
| Citric acid             | 10%           | 20 Å°C |              |
| Cresol                  | â€”           | 20 Å°C |              |
| Cyclohexanone           | 100%          | 20 Å°C |              |
| Cyclohexene             | 100%          | 20 Å°C |              |
| Diesel                  | â€”           | 20 Å°C |              |
| Diethylene oxide        | â€”           | 20 Å°C |              |
| Ethyl acetate           | 100%          | 20 Å°C |              |
| Ethyl alcohol (ethanol) | 96%           | 20 Å°C |              |
| Ethylene chloride       | 100%          | 20 Å°C |              |
| Formaldehyde, aqueous   | 40%           | 20 Å°C |              |
| Formic acid             | 10%           | 20 Å°C |              |
| Fuel oil                | â€”           | 20 Å°C |              |
| Fuel, aromatic free     | â€”           | 20 Å°C |              |
| Glycerine               | 100%          | 20 Å°C |              |
| Glycol                  | 100%          | 20 Å°C |              |

| Kemikalie                                | Concentration | Temp.  | Beständighet |
|------------------------------------------|---------------|--------|--------------|
| Heptane                                  | 100%          | 20 Å°C | ●            |
| Hydrochloric acid                        | 10%           | 20 Å°C | ●            |
| Hydrochloric acid (concentrated)         | conc.         | 20 Å°C | ●            |
| Hydrofluoric acid                        | 40%           | 20 Å°C | ●            |
| Hydrogen peroxide                        | 10%           | 20 Å°C | ●            |
| Hydrogen sulfide, aqueous                | â€”           | 20 Å°C | ●            |
| Isopropyl alcohol                        | 100%          | 20 Å°C | ●            |
| Linseed oil                              | â€”           | 20 Å°C | ●            |
| Mercurochrome                            | â€”           | 20 Å°C | ●            |
| Methyl alcohol (methanol)                | 100%          | 20 Å°C | ●            |
| Methyl ethyl ketone (MEK)                | 100%          | 20 Å°C | ●            |
| Methylene chloride                       | 100%          | 20 Å°C | ●            |
| Milk                                     | â€”           | 20 Å°C | ●            |
| Mineral oils, aromatic free              | â€”           | 20 Å°C | ●            |
| Nitric acid                              | 10%           | 20 Å°C | ●            |
| Nitric acid (50%)                        | 50%           | 20 Å°C | ●            |
| Nitrobenzene                             | â€”           | 20 Å°C | ●            |
| Oxalic acid                              | â€”           | 20 Å°C | ●            |
| Ozone (gas)                              | â‰ƒ 0.5 ppm   | 20 Å°C | ●            |
| Paraffin oil                             | 100%          | 20 Å°C | ●            |
| Perchloroethylene                        | â€”           | 20 Å°C | ●            |
| Petroleum                                | 100%          | 20 Å°C | ●            |
| Petroleum ether                          | 100%          | 20 Å°C | ●            |
| Phenol, aqueous                          | ca. 9%        | 20 Å°C | ●            |
| Phosphoric acid                          | 50%           | 20 Å°C | ●            |
| Potassium hydroxide solution             | 50%           | 20 Å°C | ●            |
| Premium fuel                             | â€”           | 20 Å°C | ●            |
| Silicone oil                             | â€”           | 20 Å°C | ●            |
| Sodium carbonate, aqueous                | â€”           | 20 Å°C | ●            |
| Sodium chloride, aqueous                 | â€”           | 20 Å°C | ●            |
| Sodium hydrogen sulfite                  | â€”           | 20 Å°C | ●            |
| Sodium hydroxide solution (60%)          | 60%           | 20 Å°C | ●            |
| Sodium hydroxide solution (caustic soda) | 15%           | 20 Å°C | ●            |
| Sodium thiosulfate                       | â€”           | 20 Å°C | ●            |

| Kemikalie             | Concentration | Temp.  | Beständighet |
|-----------------------|---------------|--------|--------------|
| Sulphuric acid        | 96%           | 20 Å°C | ●            |
| Tetrahydrofuran (THF) | 100%          | 20 Å°C | ●            |
| Toluene               | 100%          | 20 Å°C | ●            |
| Transformer oil       | â€”           | 20 Å°C | ●            |
| Trichloroethylene     | 100%          | 20 Å°C | ●            |
| Vinegar, standard     | 5-10%         | 20 Å°C | ●            |
| Water                 | â€”           | 20 Å°C | ●            |
| Xylene                | â€”           | 20 Å°C | ●            |