

PA6 E 5x1000 mm natural

Artikelnr P1000890

1. Tekniskt datablad

Egenskap	V�rde	Enhet	Standard
Densidad	1.14	g/cm���	ISO 1183
L�mite de resistencia a la tracci���n	70	MPa	DIN EN ISO 527
M��dulo de elasticidad (tracci���n)	3250	MPa	ISO 527-2
Resistencia a la tensi���n	75	MPa	ISO 527-2
Deformaci���n a la rotura	40	%	ISO 527-2
Punto de fusi���n	220	���C	ISO 3146
Temperatura de servicio m��xima (corto plazo)	160	���C	
Temperatura de funcionamiento m��xima	90.5	���C	
Temperatura m��nima	-36	���C	
Deformaci���n t��rmica (HDT/A)	70	���C	ISO 75-2
Deformaci���n t��rmica (HDT/B)	140	���C	ISO 75-2
Temperatura de ablandamiento Vicat (VST/B/50)	190	���C	ISO 306
Fuerza diel���ctrica	25	kV/mm	IEC 60243-1
Resistividad volum���trica	10������	��������	IEC 60093
Constante diel���ctrica (1 MHz)	3.7	-	IEC 60250
Constante diel���ctrica (100 Hz)	3.9	-	IEC 60250
Factor de p��rdida diel���ctrica (1 MHz)	0.0	-	IEC 60250
Factor de p��rdida diel���ctrica (100 Hz)	0.0	-	IEC 60250
Clasificaci���n de resistencia al fuego (UL 94)	3		UL 94
Resistencia a la flexi���n	76	MPa	ISO 527-2
Conductividad t��rmica	0.28	W/(m���K)	DIN 52612
Resistencia superficial	10������	���	IEC 60093
��ndice de seguimiento comparativo (CTI)	600	V	IEC 60112
Absorci���n de agua hasta la saturaci���n	2.5	%	ISO 62
Absorci���n de agua hasta la saturaci���n	9	%	ISO 62
Resistencia al impacto con entalla (Charpy)	5.5	kJ/m���	ISO 179/1eA

Egenskap	V�rde	Enhet	Standard
Coeficiente de expansi�n t�rmica	0.9	10��/K	ISO 11359
Dureza Shore D	82	� Shore D	DIN EN ISO 868
Dureza a la presi�n de bala	150	MPa	ISO 2039-1

2. Kemisk best ndighet

● Best ndig ● Delvis best ndig ● Ej best ndig

Kemikalie	Konc.	Resultat
1,4-Dioxane	100	●
2-Hydroxypropionic Acid	90	●
Acetic Acid	100	●
Acetone	100	●
Ammonia	conc.	●
Ammonium Chloride	��	●
Amyl Alcohol	��	●
Apple Juice	��	●
Benzene	��	●
Bleaching Solution	12.5 cl	●
Boric Acid	100	●
Brake Fluid	��	●
Butyl Acetate	��	●
Calcium Chloride	��	●
Carbon Disulfide	100	●
Carbon Tetrachloride	��	●
Chlorine (gas)	100	●
Chlorobenzene	100	●
Chloroform	��	●
Citric Acid	10	●
Cresol	��	●
Cyclohexanone	100	●
Cyclohexene	100	●
Diesel Fuel	��	●
Diethylene Oxide	��	●
Ethyl Acetate	100	●
Ethyl Alcohol	96	●

Kemikalie	Konc.	Resultat
Ethylene Chloride	100	
Food Oil	â€”	
Formaldehyde (aqueous)	40	
Formic Acid	10	
Frost Protection Agent	â€”	
Fuel (aromatic free)	â€”	
Glycerine	100	
Glycol	100	
Heating Oil	â€”	
Heptane	100	
Hydrochloric Acid	10	
Hydrochloric Acid (concentrated)	conc.	
Hydrofluoric Acid	40	
Hydrogen Peroxide	10	
Hydrogen Sulfide (aqueous)	â€”	
Isopropyl Alcohol	100	
Linseed Oil	â€”	
Mercurochrome	â€”	
Methyl Alcohol	100	
Methyl Ethyl Ketone (MEK)	100	
Methylene Chloride	100	
Milk	â€”	
Mineral Oils (aromatic free)	â€”	
Nitric Acid	10	
Nitric Acid	50	
Nitrobenzene	â€”	
Oxalic Acid	â€”	
Ozone Gas	â‰‰ 0.5 ppm	
Paraffine Oil	100	
Perchloroethylene	â€”	
Petroleum	100	
Petroleum Ether	100	
Phenol (aqueous)	ca. 9	
Phosphoric Acid	50	
Potassium Hydroxide liquor	50	

Kemikalie	Konc.	Resultat
Premium Fuel	â€”	●
Propyl Alcohol	â€”	●
Pyridine	â€”	●
Silicone Oil	â€”	●
Sodium Carbonate (aqueous)	â€”	●
Sodium Chloride (aqueous)	â€”	●
Sodium Hydrogen Sulfite	â€”	●
Sodium Hydroxide liquor	60	●
Sodium Hydroxide liquor	15	●
Sodium Nitrate (aqueous)	â€”	●
Sodium Thiosulfate	â€”	●
Sulfuric Acid	96	●
Tetrahydrofuran (THF)	100	●
Toluene	100	●
Transformer Oil	â€”	●
Trichloroethylene	100	●
Vinegar (standard)	5 - 10	●
Water	â€”	●
Xylene	â€”	●