

PE-1000 125x2000 mm negro

Artikelnr P2200812

● Beständig ● Delvis beständig ● Ej beständig

Kemikalie	Concentración	Temp.	Beständighet
1,4-Dioxane	100	20 °C	●
2-Hydroxypropionic acid (lactic acid)	90	20 °C	●
Acetic acid	100	20 °C	●
Acetone	100	20 °C	●
Ammonia	-	20 °C	●
Ammonium chloride	-	20 °C	●
Amyl alcohol	-	20 °C	●
Benzene	-	20 °C	●
Boric acid	100	20 °C	●
Brake fluid	-	20 °C	●
Butyl acetate	-	20 °C	●
Calcium chloride	-	20 °C	●
Citric acid	10	20 °C	●
Cresol	-	20 °C	●
Cyclohexanone	100	20 °C	●
Cyclohexene	100	20 °C	●
Diesel	-	20 °C	●
Ethyl acetate	100	20 °C	●
Ethyl alcohol (ethanol)	96	20 °C	●
Food oil	-	20 °C	●
Formaldehyde, aqueous	40	20 °C	●
Formic acid	10	20 °C	●
Frost protection agent	-	20 °C	●
Fuel oil	-	20 °C	●
Fuel, aromatic free	-	20 °C	●
Glycerine	100	20 °C	●

Kemikalie	Concentración	Temp.	Beständighet
Glycol	100	20 °C	●
Heptane	100	20 °C	●
Hydrochloric acid	10	20 °C	●
Hydrochloric acid (concentrated)	-	20 °C	●
Hydrogen peroxide	10	20 °C	●
Isopropyl alcohol	100	20 °C	●
Linseed oil	-	20 °C	●
Mercurochrome	-	20 °C	●
Methyl alcohol (methanol)	100	20 °C	●
Methylene chloride	100	20 °C	●
Milk	-	20 °C	●
Mineral oils, aromatic free	-	20 °C	●
Nitric acid	10	20 °C	●
Nitric acid	50	20 °C	●
Nitrobenzene	-	20 °C	●
Oxalic acid	-	20 °C	●
Ozone (gas)	≤ 0.5 ppm	20 °C	●
Paraffin oil	100	20 °C	●
Perchloroethylene	-	20 °C	●
Petroleum ether	100	20 °C	●
Phenol, aqueous	ca. 9	20 °C	●
Phosphoric acid	50	20 °C	●
Potassium hydroxide solution	50	20 °C	●
Premium fuel	-	20 °C	●
Propyl alcohol	-	20 °C	●
Silicone oil	-	20 °C	●
Sodium carbonate, aqueous	-	20 °C	●
Sodium chloride, aqueous	-	20 °C	●
Sodium hydrogen sulfite	-	20 °C	●
Sodium hydroxide solution (caustic soda)	60	20 °C	●
Sodium hydroxide solution (caustic soda)	15	20 °C	●
Sodium nitrate, aqueous	-	20 °C	●
Sodium thiosulfate	-	20 °C	●
Sulphuric acid	96	20 °C	●
Transformer oil	-	20 °C	●

Kemikalie	Concentración	Temp.	Beständighet
Vinegar, standard	5 - 10	20 °C	●
Water	-	20 °C	●
Xylene	-	20 °C	●