

PET 110x1000 mm negro

Nº artículo P1003526

1. Ficha técnica

Propiedad	Valor	Unidad	Norma de ensayo
Densidad	1.46	g/cm³	ISO 1183
Absorción de agua hasta la saturación	0.02	%	ISO 62
Absorción de agua hasta la saturación	0.02	%	ISO 62
Límite de resistencia a la tracción	52	MPa	ISO 527
Módulo de elasticidad (tracción)	3400	MPa	ISO 527-2
Resistencia a la tensión	58	MPa	ISO 527
Deformación a la rotura	5	%	ISO 527-2
Resistencia a la flexión	75.25	MPa	ISO 178
Resistencia al impacto con entalla (Charpy)	90	kJ/m²	ISO 180
Resistencia al impacto (Charpy)	37	kJ/m²	ISO 179/1eU
Dureza Shore D	77	° Shore D	ISO 868
Dureza Rockwell	112	M-scale	
Dureza a la presión de bala	166	MPa	ISO 2039
Punto de fusión	224	°C	ISO 3146
Temperatura de servicio máxima (corto plazo)	138.75	°C	UL746B
Temperatura de funcionamiento máxima	97	°C	
Temperatura mínima	-25	°C	
Deformación térmica (HDT/A)	85	°C	ISO 75
Deformación térmica (HDT/B)	100	°C	ISO 75
Temperatura de ablandamiento Vicat (VST/B/50)	219	°C	ISO 306
Conductividad térmica	0.33	W/(m·K)	DIN 52612
Coefficiente de expansión térmica	0.8	10 ⁻⁴ /K	DIN 11359
Fuerza dieléctrica	22	kV/mm	IEC 60243-1
Resistividad volumétrica	10 ¹⁸	Ω·cm	DIN EN 62631-3-1
Constante dieléctrica (1 MHz)	3.3	-	IEC 60250

Sustancia química	Concentración	Resist.
Carbon tetrachloride	—	
Chlorobenzene	100%	
Chlorobenzene	100	
Chlorobenzene	100	
Chloroform	—	
Chloroform	—	
Citric acid	10	
Citric acid	10	
Diesel	—	
Diesel	—	
Diethylene oxide	—	
Diethylene oxide	—	
Ethyl acetate	100	
Ethyl acetate	100	
Ethyl alcohol (ethanol)	96	
Ethyl alcohol (ethanol)	96%	
Ethyl alcohol (ethanol)	96	
Ethylene chloride	100	
Ethylene chloride	100	
Food oil	—	
Food oil	—	
Food oil	—	
Formic acid	10	
Formic acid	10	
Frost protection agent	—	
Frost protection agent	—	
Fuel oil	—	
Fuel oil	—	
Fuel, aromatic free	—	
Fuel, aromatic free	—	
Glycerine	100%	
Glycerine	100	

Sustancia química	Concentración	Resist.
Glycerine	100	
Glycol	100	
Glycol	100	
Heptane	100	
Heptane	100	
Hydrochloric acid	conc.	
Hydrochloric acid	10	
Hydrochloric acid	conc.	
Hydrochloric acid	10	
Hydrochloric acid (concentrated)	conc.	
Hydrofluoric acid	40	
Hydrofluoric acid	40%	
Hydrofluoric acid	40	
Hydrogen peroxide	10	
Hydrogen peroxide	10	
Hydrogen sulfide, aqueous	—	
Isopropyl alcohol	100	
Isopropyl alcohol	100	
Isopropyl alcohol	100%	
Linseed oil	—	
Linseed oil	—	
Mercurochrome	—	
Methyl alcohol (methanol)	100	
Methyl alcohol (methanol)	100%	
Methyl alcohol (methanol)	100	
Methyl ethyl ketone (MEK)	100	
Methyl ethyl ketone (MEK)	100	
Methylene chloride	100	
Methylene chloride	100	
Milk	—	
Milk	—	
Mineral oils, aromatic free	—	

Sustancia química	Concentración	Resist.
Mineral oils, aromatic free	—	●
Nitric acid	50	●
Nitric acid	10	●
Nitric acid	10%	●
Nitric acid	10	●
Nitric acid	50	●
Paraffin oil	100	●
Paraffin oil	100	●
Perchloroethylene	—	●
Perchloroethylene	—	●
Petroleum	100	●
Petroleum	100%	●
Petroleum ether	100	●
Petroleum ether	100%	●
Petroleum ether	100	●
Phenol, aqueous	ca.9	●
Phosphoric acid	50	●
Phosphoric acid	50	●
Potassium hydroxide solution	50	●
Potassium hydroxide solution	50	●
Premium fuel	—	●
Premium fuel	—	●
Propyl alcohol	—	●
Propyl alcohol	—	●
Silicone oil	—	●
Silicone oil	—	●
Sodium carbonate, aqueous	—	●
Sodium carbonate, aqueous	—	●
Sodium chloride, aqueous	—	●
Sodium chloride, aqueous	—	●
Sodium hydrogen sulfite	—	●
Sodium hydrogen sulfite	—	●

Sustancia química	Concentración	Resist.
Sodium hydrogen sulfite	—	●
Sodium hydroxide solution (caustic soda)	60	●
Sodium hydroxide solution (caustic soda)	60	●
Sodium hydroxide solution (caustic soda)	15	●
Sodium hydroxide solution (caustic soda)	15	●
Sodium nitrate, aqueous	—	●
Sodium thiosulfate	—	●
Sulphuric acid	96	●
Sulphuric acid	96	●
Tetrahydrofuran (THF)	100	●
Tetrahydrofuran (THF)	100	●
Toluene	100%	●
Toluene	100	●
Toluene	100	●
Transformer oil	—	●
Transformer oil	—	●
Trichloroethylene	100	●
Trichloroethylene	100	●
Vinegar, standard	5-10%	●
Vinegar, standard	5-10	●
Vinegar, standard	5-10	●
Water	—	●
Water	—	●
Xylene	—	●
Xylene	—	●