



PEI 101,6x1220 mm ruskea

Artikelnr P1003401

Best ndig

Delvis best ndig

Ej best ndig

Kemikalie	Pitoisuus	Temp.	Best�ndighet
1,4-Dioxane	100%	20 �C	
Acetone	100%	20 �C	
Ammonia	concentrated	20 �C	
Ammonium chloride	��	20 �C	
Apple juice	��	20 �C	
Brake fluid	��	20 �C	
Calcium chloride	��	20 �C	
Chlorobenzene	100%	20 �C	
Chloroform	��	20 �C	
Citric acid	10%	20 �C	
Diesel	��	20 �C	
Ethyl acetate	100%	20 �C	
Ethyl alcohol (ethanol)	96%	20 �C	
Ethylene chloride	100%	20 �C	
Food oil	��	20 �C	
Formaldehyde (aqueous)	40%	20 �C	
Formic acid	10%	20 �C	
Frost protection agent	��	20 �C	
Fuel (aromatic free)	��	20 �C	
Fuel oil	��	20 �C	
Glycerine	100%	20 �C	
Glycol	100%	20 �C	
Heptane	100%	20 �C	
Hydrochloric acid	10%	20 �C	
Hydrochloric acid (concentrated)	concentrated	20 �C	
Methyl alcohol (methanol)	100%	20 �C	
Methyl ethyl ketone (MEK)	100%	20 �C	

Kemikalie	Pitoisuus	Temp.	Beständighet
Methylene chloride	100%	20 Å°C	●
Milk	â€”	20 Å°C	●
Mineral oil (aromatic free)	â€”	20 Å°C	●
Nitric acid	10%	20 Å°C	●
Nitric acid	50%	20 Å°C	●
Paraffin oil	100%	20 Å°C	●
Phosphoric acid	50%	20 Å°C	●
Potassium hydroxide solution	50%	20 Å°C	●
Premium fuel	â€”	20 Å°C	●
Pyridine	â€”	20 Å°C	●
Silicone oil	â€”	20 Å°C	●
Sodium carbonate (aqueous)	â€”	20 Å°C	●
Sodium chloride (aqueous)	â€”	20 Å°C	●
Sodium hydrogen sulfite	â€”	20 Å°C	●
Sulphuric acid	96%	20 Å°C	●
Tetrahydrofuran (THF)	100%	20 Å°C	●
Toluene	100%	20 Å°C	●
Transformer oil	â€”	20 Å°C	●
Trichloroethylene	100%	20 Å°C	●
Vinegar (standard)	5-10%	20 Å°C	●
Water	â€”	20 Å°C	●