



POM CGL 180/90x3000 mm blå

Artikelnr P1008272

Beständig Delvis beständig Ej beständig

Kemikalie	Konsentrasjon	Temp.	Beständighet
1,4-Dioxan	100%	20 Å°C	
2-Hydroxypropionic Acid	90%	20 Å°C	
Acetic Acid	100%	20 Å°C	
Aceton	100%	20 Å°C	
Ammoniak	conc.	20 Å°C	
Ammonium Chloride	â€	20 Å°C	
Amyl Alcohol	â€	20 Å°C	
Apple Juice	â€	20 Å°C	
Bensen	â€	20 Å°C	
Bleaching Solution	12.5 cl	20 Å°C	
Boric Acid	100%	20 Å°C	
Brake Fluid	â€	20 Å°C	
Br�nsle, aromatfritt	â€	20 Å°C	
Butyl Acetate	â€	20 Å°C	
Calcium Chloride	â€	20 Å°C	
Carbon Disulfide	100%	20 Å°C	
Carbon Tetrachloride	â€	20 Å°C	
Citric Acid	10%	20 Å°C	
Cyklohexanon	100%	20 Å°C	
Cyklohexen	100%	20 Å°C	
Diesel Fuel	â€	20 Å°C	
Diethylene Oxide	â€	20 Å°C	
Eddik, standard	5-10%	20 Å°C	
Ethyl Acetate	100%	20 Å°C	
Ethyl Alcohol	96%	20 Å°C	
Ethylene Chloride	100%	20 Å°C	
Fenol, vattenl.	ca. 9%	20 Å°C	

[illegible]

Kemikalie	Konsentrasjon	Temp.	Best�ndighet
Potassium Hydroxide liquor	50%	20 �C	
Premium Fuel	��	20 �C	
Propyl Alcohol	��	20 �C	
Pyridin	��	20 �C	
Silicone Oil	��	20 �C	
Sodium Carbonate, aqueous	��	20 �C	
Sodium Chloride, aqueous	��	20 �C	
Sodium Hydrogen Sulfite	��	20 �C	
Sodium Hydroxide liquor (15%)	15%	20 �C	
Sodium Hydroxide liquor (60%)	60%	20 �C	
Sodium Nitrate, aqueous	��	20 �C	
Sodium Thiosulfate	��	20 �C	
Sulfuric Acid	96%	20 �C	
Tetrahydrofuran, THF	100%	20 �C	
Toluen	100%	20 �C	
Transformer Oil	��	20 �C	
Trikloreten	100%	20 �C	
Vann	��	20 �C	
Xylen	��	20 �C	