



Artikelnr P2201609

Egenskap	V�rde	Enhet	Standard
Tetthet	0.9	g/cm� ³	DIN EN ISO 1183-1
StrekkgrenseSpenning	24	MPa	DIN EN ISO 527
Elastisitetsmodul (trek)	1241.2	MPa	DIN EN ISO 527
Brottsdeformasjon	50	%	DIN EN ISO 527
Smeltepunkt	164	��C	ISO 11357-3
Maksimal drifttemperatur (kortvarig)	116	��C	
Maksimal driftstemperatur	75	��C	
Minstemperatur	-23	��C	
Vicat-mykningstemperatur (VST/B/50)	87	��C	DIN EN ISO 306
Dielektrisk Styrke	40	kV/mm	IEC 60243
VolumResistivit�t	10� ¹⁴ �	��cm	DIN EN 62631-3-1
Dielektrisk konstant (1 MHz)	2.48	-	IEC 60250
Dielektrisk dissipasjonsfaktor (1 MHz)	0.0	-	IEC 60250
Dielektrisk tapfaktor (100 Hz)	0.0	-	IEC 60250
Termisk konduktivit�t	0.2	W/(m��K)	DIN 52612-1
Overflatemotstand	10� ¹⁴ �	��	DIN EN 62631-3-2
Sammenligningskrypstr�msindeks (CTI)	600	V	IEC 60112
Fuktabsorpsjon til metning	0.1	%	DIN EN ISO 62
Vannabsorpsjon til metning	0.1	%	DIN EN ISO 62
Sk��ret slagfasthet (Charpy)	4	kJ/m� ²	DIN EN ISO 179
Termisk utvidelseskoeffisient	0.0	10� ⁻⁶ /K	DIN 53752
Hardhet Shore D	67.25	�� Shore D	DIN EN ISO 868
Kuletrykkshardhet	50	MPa	DIN EN ISO 2039-1

● Beständigt
 ● Delvis beständigt
 ● Ej beständigt

Kemikalie	Konc.	Resultat
1,4-Dioxan	100	
2-Hydroxypropionic Acid	90	
Acetic Acid	100	
Aceton	100	
Ammoniak	â€	
Ammonium Chloride	â€	
Amyl Alcohol	â€	
Apple Juice	â€	
Bensen	â€	
Bleaching Solution	â€	
Boric Acid	100	
Brake Fluid	â€	
Br�nsle, aromatfritt	â€	
Butyl Acetate	â€	
Calcium Chloride	â€	
Carbon Disulfide	100	
Carbon Tetrachloride	â€	
Citric Acid	10	
Cyklohexanon	100	
Cyklohexen	100	
Diesel Fuel	â€	
Diethylene Oxide	â€	
Eddik, standard	5 - 10	
Ethyl Acetate	100	
Ethyl Alcohol	96	
Ethylene Chloride	100	
Fenol, vattenl.	ca. 9	
Food Oil	â€	
Formaldehyd, vattenl.	40	
Formic Acid	10	
Frost Protection Agent	â€	
Glycerin	100	
Glykol	100	
Heating Oil	â€	
Heptan	100	

Kemikalie	Konc.	Resultat
Hydrochloric Acid	10	●
Hydrochloric Acid (concentrated)	â€”	●
Hydrofluoric Acid	40	●
Hydrogen Peroxide	10	●
Hydrogen Sulfide, aqueous solution	â€”	●
Isopropyl Alcohol	100	●
Klor (gas)	100	●
Klorbensen	100	●
Kloroform	â€”	●
Kresol	â€”	●
Linseed Oil	â€”	●
Melk	â€”	●
Merkurokrom	â€”	●
Methyl Alcohol	100	●
Methyl Ethyl Ketone (MEK)	100	●
Methylene Chloride	100	●
Mineral Oils (aromatic free)	â€”	●
Nitric Acid	50	●
Nitric Acid	10	●
Nitrobensen	â€”	●
Oxalic Acid	â€”	●
Ozone Gas	â‰¥ 0.5 ppm	●
Paraffine Oil	100	●
Perkloretylen	â€”	●
Petroleum	100	●
Petroleum Ether	100	●
Phosphoric Acid	50	●
Potassium Hydroxide liquor	50	●
Premium Fuel	â€”	●
Propyl Alcohol	â€”	●
Pyridin	â€”	●
Silicone Oil	â€”	●
Sodium Carbonate, aqueous	â€”	●
Sodium Chloride, aqueous	â€”	●
Sodium Hydrogen Sulfite	â€”	●

Kemikalie	Konc.	Resultat
Sodium Hydroxide liquor	15	●
Sodium Hydroxide liquor	60	●
Sodium Nitrate, aqueous	â€”	●
Sodium Thiosulfate	â€”	●
Sulfuric Acid	96	●
Tetrahydrofuran (THF)	100	●
Toluen	100	●
Transformer Oil	â€”	●
Trikloreten	100	●
Vann	â€”	●
Xylen	â€”	●